



Technical features



Cavity	(For dimensions see catalogue 17.000)	S 50/2
Max. flow	(l/min.)	160
Max. inlet pressure	(bar)	350
Max. pressure on line 2	(bar)	350
Fluid viscosity range	(cSt)	2.8 – 380
Fluid temperature range	(°C)	–20 +80
Mass	(kg)	0.910
Cracking pressure 95% of setting value		
Reseat pressure 75% of setting value		
Cracking pressure defined with 1 l/min.		
Standard setting obtained with 10 l/min.		
Hydraulic fluid; mineral oil HM and HV ISO 6074		
Recommended filtration; 19/15 ISO 4466 (25 μ absolutes)		
Standard seals in Polyurethane and Buna N		

Dimensions



Ordering informations

LPB 50/D–N

LPB 50 = Valve type



Standard springs

Type	Setting range	Factory set
U	10 – 105 bar	70 bar
D	70 – 210 bar	140 bar
T	140 – 350 bar	280 bar

Adjustment type

N = Standard adjustment



Codes:

LPB 50/U–N	51 011 100
LPB 50/D–N	51 011 101
LPB 50/T–N	51 011 102

External seals kit 90 620 106

LPB 50 valves can be assembled on standard bodies 50–L0 series; for dimensions see catalogue 16.010